

Thermo-Electro-Mechanical Modelling of Spark Plasma Sintering within Discrete Element Framework

Jerzy Rojek^{1*}, Fatima Nisar¹, Szymon Nosewicz¹, Marcin Chmielewski², Kamil Kaszyca²

¹Institute of Fundamental Technological Research, Polish Academy of Sciences, Warsaw, Poland
e-mail: fnisar@ippt.pan.pl, jrojek@ippt.pan.pl, snosew@ippt.pan.pl

²Lukasiewicz Institute of Microelectronics and Photonics, Warsaw, Poland
e-mails: marcin.chmielewski@imif.lukasiewicz.gov.pl, kamil.kaszyca@imif.lukasiewicz.gov.pl

KEYWORDS: *Discrete element method (DEM), Spark Plasma Sintering, conductive materials, thermoelectromechanical model*

Spark Plasma Sintering (SPS) is a powder consolidation process that combines mechanical pressure with rapid Joule heating induced by electric current. This facilitates the consolidation and densification of particulate materials, making SPS a sustainable and energy-efficient technique. Initially, the powder consists of loosely bonded particles. As the process progresses, the particles become connected through necks, which grow over time due to diffusion and mass transport. The complexity of the SPS process lies in the strong interdependence of electrical, thermal and mechanical phenomena. Accurate modelling of this process requires a fully coupled multiphysics approach.

In this work, a microscopic thermo-electro-mechanical model is developed within the Discrete Element Method (DEM) framework. DEM enables microscopic analysis by treating each particle as a discrete element, thereby enabling precise representation of microscopic interactions. The model is based on sintering geometry, assuming cylindrical neck formation between spherical particles. Individual models for electrical, thermal, and mechanical behaviour are first validated separately, and then integrated into a fully coupled model. Thermal and electrical models were presented in [1, 2], in which effective properties were evaluated and validated against experimental measurements. A coupled thermo-electric model was presented in [3], where it was shown that Joule heating, generated due to current flow, tends to concentrate in smaller particles but is effectively conducted throughout the sample, leading to a relatively uniform temperature rise. Finally, the effect of densification on heating rate was analysed. Herein, the coupled thermo-electric model will be integrated with the mechanical model to study the multiphysics phenomena during the SPS process.

ACKNOWLEDGEMENT: Research funded by National Science Centre, Poland, project no. 2019/35/B/ST8/03158

- [1] F. Nisar, J. Rojek, S. Nosewicz, K. Kaszyca, and M. Chmielewski, “Evaluation of effective thermal conductivity of sintered porous materials using an improved discrete element model”, *Powder Technology*, 437, 119546 (2024).
- [2] F. Nisar, J. Rojek, S. Nosewicz, J. Szczepański, K. Kaszyca, and M. Chmielewski, “Discrete element model for effective electrical conductivity of spark plasma sintered porous materials”, *Computational Particle Mechanics*, 11, 2191-2201 (2024).
- [3] F. Nisar, J. Rojek, S. Nosewicz, K. Kaszyca, and M. Chmielewski, “Coupled thermo-electric discrete element model for spark plasma sintering”, *Powder Technology*, 458, 120957 (2025).